

SINGLE CORE XLPE-SCREENED/PVC/AWA/PVC 15KV BS6622 IEC60502-2

Plain annealed circular compacted copper conductor/semi conducting layer/XLPE/Semi-conducting layer/copper tape screened/PVC extruded bedded/Aluminium wire armoured/PVC sheathed. 8.7/15KV volts grade to BS6622 & IEC60502-2. Sheath colour:Red (Black on request)

SIZE SQ.MM	REACTANCE AT 50HZ	IMPEDANCE AT 50HZ	MAX CAPACITANCE pF/m	MINIMUM BENDING RADIUS MM	THICKNESS OF PVC BEDDING MM	THICKNESS OF PVC SHEATH MM	APPROX OVERALL DIAMETER MM	WEIGHT KG/M	BATT PART NO RED	BATT PART NO BLACK
150	121	198	301	700	1.2	2.1	37.8	2.7		56256
240	113	148	363	800	1.2	2.3	42.4	3.8		
300	108	133	398	850	1.2	2.3	44.7	4.5		56259
400	107	124	439	900	1.3	2.5	49.0	5.6		
500	103	114	483	950	1.3	2.6	52.1	6.7		
630	99.5	107	534	1050	1.4	2.7	55.9	8.2	56690	

