

## 16-2-S PVC/Foil Screened/PVC Grey



<b>Conductor:</b>	Tinned annealed flexible copper
<b>Insulation:</b>	PVC (Polyvinyl Chloride)
<b>Core identification:</b>	Single and Bi-coloured Cores 2 to 36 core in acc.Def Stan 61-12. 50 core and above to BATT Cables Colour code.
<b>Screen:</b>	CAM (Collective aluminium mylar) including drain wire
<b>Sheath:</b>	PVC (Polyvinyl Chloride)
<b>Colour:</b>	Grey
<b>Voltage:</b>	440v
<b>Operating temperature:</b>	80°C, Minimum bending: -5°C
<b>Standards:</b>	Defence standard 61-12 Part 5: Wires, cords & cables, electrical -metric units. Part 5 - cables, special purpose, electrical & cables, power, electrical (small multicore cables)

No of cores	Cable Ref	Size mm	Strand mm	Drain wire	Sheath thickness mm	Overall diameter mm	Weight kg/km	BATT Part No.
2	16-2-2S	0.5	16/0.2	16 x 0.2	0.6	4.8	37	35119
3	16-2-3S	0.5	16/0.2	16 x 0.2	0.8	6.0	55	35210
4	16-2-4S	0.5	16/0.2	16 x 0.2	0.8	6.2	60	35149
6	16-2-6S	0.5	16/0.2	16 x 0.2	0.8	7.2	81	35150
8	16-2-8S	0.5	16/0.2	16 x 0.2	-	8.2	104	35214
12	16-2-12S	0.5	16/0.2	16 x 0.2	-	9.7	132	35106
15	16-2-15S	0.5	16/0.2	16 x 0.2	-	12.6	198	35164
18	16-2-18S	0.5	16/0.2	16 x 0.2	-	-	-	-
25	16-2-25S	0.5	16/0.2	16 x 0.2	-	-	-	35107