





RG11 Cable

CONSTRUCTION

Inner Conductor	7/0.4mm tinned copper
Insulation	7.25+/- 0.05mm solid PE
Braid	bare copper wire (coverage: 96%)
Sheath	10.1+/- 0.20mm black PVC

BATT Part Number 49056



CHARACTERISTICS

Impedance:	75+/-3 Ohm
Capacitance	67+/-5 pF/M
Attenuation	100MHz 9.2 dB/100m
20 degree C	500MHz 20dB/100m
	1000MHz 28.5 dB/100m
Velocity ratio	66.7%
Rated voltage	30V
Rated temperature	70 deg C
Max conductor DC resistance at 20 deg C	21.17 Ohm/km

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Erith: 01322 441165

Copenhagen: +45 3965 6650

Birmingham: 0121 313 2870

Leeds: 0113 253 3565

Houston: + 1 713 590 1100

Bristol: 0117 966 6333

Manchester: 01204 793111

Mainz: +49 6131 6273874

Cardiff: 02920 450044

Peterborough: 01733 558485

Rotterdam: + 31 186 622311

Edinburgh: 0131 333 4400

Teesside: 01642 678633