

318* TRS TRAILING FLEXIBLE H05RR-F

Annealed flexible copper conductors, EI4 60°C Rubber insulated, Tough Rubber (TR) sheathed. 300/500 volts grade, to BS7919 & BS6500

DIN VDE 0282-4

(* denotes quantity of cores)

For an explanation of harmonised codes see table in technical section

SIZE SQ.MM	NUMBER OF CORES	RT OF INSULATION MM	NOMINAL DIAMETER OVER LAID UP CORES MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
**0.5	2	0.6	4.4	6.1	53
0.75	2	0.6	4.8	6.6	63
1.0	2	0.6	5.2	7.1	77
1.5	2	0.8	6.6	8.7	115
2.5	2	0.9	7.8	10.3	165
**0.5	3	0.6	4.8	6.9	62
0.75	3	0.6	5.2	7.2	78
1.0	3	0.6	5.7	7.5	90
1.5	3	0.8	7.2	9.2	135
2.5	3	0.9	8.5	11.0	195
0.75	4	0.6	5.8	7.8	94
1.0	4	0.6	6.3	8.2	110
1.5	4	0.8	8.0	10.3	170
2.5	4	0.9	9.5	12.3	245
0.75	5	0.6	6.5	7.6	110
1.0	5	0.6	7.1	8.0	130
1.5	5	0.8	9.0	9.8	195
2.5	5	0.9	10.6	11.9	290



BATT PART NUMBER TABLE				
	2 Core	3 Core	4 Core	5 Core
Size SQ.MM	Black	Black	Black	Black
**0.5	22128	22124	-	-
0.75	22133	22174	22244	22125
1.0	22138	22181	22245	22126
1.5	22143	22189	22246	22431
2.5	22146	22195	22259	22405

Operating temperature: Maximum 60°.

** H05RR-F does not apply (National type)

Conductor identification:
 Two Core - Brown & Blue
 Three Core - Brown, Blue & Green/Yellow
 Four Core - Brown, Grey, Black & Green/Yellow
 Five Core - Brown, Blue, Grey, Black & Green/Yellow

Conductor: Class 5 flexible

Minimum bending radius: 6 x overall diameter

Applications: suitable for domestic premises, kitchens and offices for supplying portable appliances eg vacuum cleaner, iron

battindustrial.sales@batt.co.uk