



318TRS Rubber Cable

Applications:	Flexible rubber cable suitable for domestic and office environments. Suitable for domestic premises, kitchens and offices for supplying portable appliance.
Conductors:	Annealed flexible copper
Insulation:	EPR (Ethylene propylene rubber) or VIR (Vulcanised insulated rubber) more commonly known as VRI
Core identification:	2 core: Blue & brown 3 core: Blue, brown & green/yellow 4 core: Black, brown, grey & green/yellow 5 core: Black, blue, brown, grey & green/yellow
Sheath/Jacket:	TRS (Tough rubber sheath)
Colour:	Black
Voltage:	300/500v
Operating temperature:	Maximum 70°C, minimum bending -30°C
Minimum bending radius:	6 x overall diameter
Standards:	BS6500: flexible electric cables for use with appliances and equipment intended for domestic, office and similar environments BS7919: flexible electric cables for use with appliances and equipment intended for industrial and similar environments



Size sq.mm	Number of cores	RT of insulation mm	Nom diameter over laid up cores mm	Nom overall diameter mm	Weight kg/km	BATT Part no Black
**0.5	2	0.6	4.4	6.1	53	22128
0.75	2	0.6	4.8	6.6	63	22133
1.0	2	0.6	5.2	7.1	77	22138
1.5	2	0.8	6.6	8.7	115	22143
2.5	2	0.9	7.8	10.3	165	22146
**0.5	3	0.6	4.8	6.9	62	22124
0.75	3	0.6	5.2	7.2	78	22174
1.0	3	0.6	5.7	7.5	90	22181
1.5	3	0.8	7.2	9.2	135	22189
2.5	3	0.9	8.5	11.0	195	22195
0.75	4	0.6	5.8	7.8	94	22244
1.0	4	0.6	6.3	8.2	110	22245
1.5	4	0.8	8.0	10.3	170	22246
2.5	4	0.9	9.5	12.3	245	22259
0.75	5	0.6	6.5	7.6	110	22125
1.0	5	0.6	7.1	8.0	130	22126
1.5	5	0.8	9.0	9.8	195	22431
2.5	5	0.9	10.6	11.9	290	22405

** HO5RR-F Does not apply (National type)

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.