

## 400Hz PVC

Class 2 copper conductor, XLPE insulation, PVC, Aluminium Wire Armoured, PVC Sheath  
Volts Grade 0.6/1KV to BS5467 (400Hz) Sheath colour: Orange

NUMBER OF CORES	SIZE MM	BATT PART NUMBER
3	70	56407
6	70	56383
6	120	56406
7	70	56385



**Standard:** BS5467: Electric cables. Thermosetting insulated, armoured cables for voltages of 600/1000V and 1900/3300V

**Applications:** airport cable, power supply to aircraft, computer systems and radar stations. Suitable for direct burial

## 400Hz LSZH

Class 2 copper conductor, XLPE insulation,LSZH, Aluminium Wire Armoured, LSZH Sheath  
Volts Grade 0.6/1KV to BS6724 (400Hz) IEC60332-3 Sheath colour: Orange

NUMBER OF CORES	SIZE MM	BATT PART NUMBER	OVERALL DIAMETER MM	TOTAL WEIGHT KG/KM
3	70	56306		
3	120	56309		
7	35	56413	36.6	3355
7	35	56338 (Black)	36.6	3355

Conductor Diameter: 6.80mm  
Insulation Thickness: 0.9mm  
Armour Thickness: 1.2mm  
Sheath Thickness: 2.1mm

**Standard:** BS5467: Electric cables. Thermosetting insulated, armoured cables for voltages of 600/1000V and 1900/3300V

**Applications:** airport cable, power supply to aircraft, computer systems and radar stations. Suitable for direct burial