



## 400Hz Cable

### 400Hz PVC Cable

Class 2 copper conductor, XLPE insulation, PVC, Aluminium Wire Armoured, PVC Sheath

**Application:** Airport cable, power supply to aircraft, computer systems and radar stations. Suitable for direct burial.

**Sheath colour:** Orange

**Volts grade:** 0.6 / 1Kv to BS5467 (400Hz)

**Standards:** BS5467: Electric cables. Thermosetting insulated, armoured cables for voltages of 600 / 1000V and 1900/3300V



Number of cores	Size mm	BATT part number
3	70	56407
6	70	56383
6	120	56406
7	70	56385

### 400Hz LSZH

Class 2 copper conductor, XLPE insulation, LSZH, Aluminium Wire Armoured, LSZH Sheath.

**Application:** Airport cable, power supply to aircraft, computer systems and radar stations. Suitable for direct burial

**Sheath colour:** Orange

**Volts grade:** 0.6 / 1Kv to BS6724 (400Hz)

**Conductor diameter:** 6.80mm

**Insulation thickness:** .9mm

**Armour thickness:** 1.2mm

**Sheath thickness:** 2.1mm

**Standards:** BS5467: Electric cables. Thermosetting insulated, armoured cables for voltages of 600 / 1000V and 1900/3300V

Number of cores	Size mm	Overall Diameter mm	Total weight kg/km	BATT Part Number
3	70			56306
3	120			56309
7	35	36.6	3355	56413
7	35	36.6	3355	56338 (Black)