



6491X H05V-U Cable 300/500V BS6004

Applications:	As single core for internal wiring of devices as well as protected laying within and on luminaires. Laying within pipes on wall and in wall permitted for signal facilities.
Conductor:	Copper conductor, bare single wire according to VDE 0295 cl. 1
Insulation:	PVC TI1 according to HD 21.1 S3
Core identification:	According to VDE 0293
Nominal voltage U₀/U	300 / 500 volts
Test voltage:	2000v
Temperature range:	Fixed installation: -40°C to 70°C Flexing: 5°C to 70°C
Min bending radius:	4 x cable diameter
Standards:	This product corresponds to the directive 2006/95/EGCE (low voltage directive). BS6004 Electric cables. PVC insulated, non-armoured cables for voltages up to and including 450/750V, for electric power, lighting and internal wiring

Size sq mm	Class off conductor	Max diameter over conductor mm	RT of insulation	Nominal overall diameter mm	Weight kg/km	Colour	BATT part number
0.5	1	-	-	2.05	-	Black	16760
0.5	1	-	-	2.05	-	Yellow	16761
0.5	1	-	-	2.05	-	White	16759
0.5	1	-	-	2.05	-	Grey	-
1.0	1	1.13	0.6	2.4	14	Red	16019
1.0	1	1.13	0.6	2.4	14	Black	16020
1.0	1	1.13	0.6	2.4	14	Grn/Yellow	16025
1.0	1	1.13	0.6	2.4	14	Blue	16021
1.0	1	1.13	0.6	2.4	14	Yellow	16022
1.0	1	1.13	0.6	2.4	14	Brown	16444
1.0	1	1.13	0.6	2.4	14	White	16023
1.0	1	1.13	0.6	2.4	14	Grey	-
1.0	1	1.13	0.6	2.4	14	Pink	-

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.

www.batt.co.uk

battindustrial.sales@batt.co.uk