

7-2-C Part 4 (Screened): PVC/TCWB/PVC

Conductor:	Tinned annealed flexible copper
Conductor Identification:	Single and Bi-coloured Cores 2 to 36 core in acc.Def Stan 61-12. 50 core and above to BATT Cables Colour code.
Insulation:	PVC (polyvinyl chloride)
Screen:	TCWB (Tinned copper wire braid)
Sheath:	PVC (Polyvinyl Chloride)
Colour:	Black
Size:	0.22mm ²
Stranding:	7/.2
Diameter over conductor:	0.6mm
RT of insulation:	0.3mm
Nom overall diameter of core:	1.20mm
Current rating:	1.0 amps
Max conductor resistance at 20°C:	92 ohms DC/KM
Voltage:	440v
Min bending radius:	6 x overall diameter
Operating Temperature:	70°C, Minimum bending: 0°C
Standards:	Defence standard 61-12 Part 4: Wires, cords & cables, electrical -metric units. Part 4 - cables, special purpose, electrical (sub miniature electrical cables)



No of cores	Nato No. 6145-99-110-	Cable ref	Diameter over laid up cores mm	Diameter of braid wire mm	Diameter over collective screen mm	Nominal overall diameter mm	Weight kg/km	BATT Part No
2	8622	7-2-2C	2.4	0.1	2.9	3.9	23	35012
3	8625	7-2-3C	2.6	0.1	3.1	4.1	27	35013
4	8628	7-2-4C	2.9	0.1	3.4	4.4	32	35014
6	8631	7-2-6C	3.6	0.15	4.4	5.6	55	35015
**8	-	7-2-8C	4.0	0.15	4.8	5.9	69	35016
12	8634	7-2-12C	5.0	0.15	5.8	6.9	83	35017
**15	-	7-2-15C	5.5	0.15	6.3	7.6	97	35157
18	8637	7-2-18C	6.0	0.15	6.8	8.2	110	35018
**20	-	7-2-20C	6.4	0.15	7.2	8.5	120	35019
25	8640	7-2-25C	7.2	0.15	8.0	9.5	150	35020
36	8643	7-2-36C	8.4	0.15	9.2	10.8	200	35021
50	8646	7-2-50C	10.0	.20	11.0	12.6	270	35023
60	8649	7-2-60C	10.8	0.20	11.8	13.4	310	35025

** Generally to Def Stan 61-12 Part 4

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.