




8102 LSZH Cable

CONSTRUCTION

Conductor	24 awg stranded tinned copper
Insulation	Polypropylene
Pair	2 twisted pairs: white/blue & blue/white, white/orange & orange/white
Shield	Overall aluminium-polyester foil, 100% coverage
Drain Wire	24 awg stranded tinned copper
Braid	Tinned copper wire braid (65% coverage)
Sheath	Black LSZH
	Overall diameter: 6.85+/- 0.20mm

BATT Part Number 91424



CHARACTERISTICS

Nominal Capacitance	41.000 pF/m
Nominal Conductor DCR	78.74 Ohm/km
Nominal Velocity of Propagation	78.0%
Nominal Impedance	100.0 Ohms

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650