



8720 Cable

CONSTRUCTION

Conductor	14 awg (19/0.361mm) stranded tinned copper
Insulation	Colour code:black & clear PE, nominal thickness: 0.813mm
Pair	1 twisted pair
Shield	Overlapped aluminium-polyester foil, 100% coverage
Drain Wire	16 awg (19/0.287mm) stranded tinned copper
Sheath	Grey PVC, nominal thickness 0.89mm
	Overall diameter: 9.02+/- 0.20mm

BATT Part Number 91112



CHARACTERISTICS

Nominal Capacitance	24.000 pF/ft
Nominal Conductor DCR	2.900 Ohm/1000ft
Nominal Velocity of Propagation	66.0%
Nominal Impedance	58.0 Ohms

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650