



9501 LSZH Cable

CONSTRUCTION

Conductor	24awg (7/0.2mm) stranded tinned copper
Insulation	Colour code:black & red PVC, nominal thickness: 0.254mm
Pairs	1 twisted pair
Shield	Overall overlapped aluminium-polyester foil (100% coverage)
Drain Wire	24awg (7/0.2mm) stranded tinned copper
Sheath	Grey or violet LSZH, nominal thickness 0.81mm Overall diameter: 3.96+/- 0.20mm

BATT Part Number, grey 91361

BATT Part Number, violet 91125



CHARACTERISTICS

Nominal Capacitance	40.000 pF/ft
Nominal Conductor DCR	2400 Ohm/1000ft
Nominal Velocity of Propagation	60%
Nominal Impedance	75 Ohms

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650