



9502 LSZH Cable

CONSTRUCTION

Conductor	24 awg (7/0.20mm) stranded tinned copper
Insulation	Black, white, black, red SR-PVC nominal thickness: 0.254mm
Pair	2 twisted pairs, black & red, black & white
Shield	Overall overlapped aluminium-polyester foil, 100% coverage
Drain Wire	24 awg (7/0.20mm) stranded tinned copper
Sheath	Violet LSZH, nominal thickness 0.81mm Overall diameter: 5.64+/- 0.20mm

BATT Part Number 91166
BATT Part Number, grey sheath 91362



CHARACTERISTICS

Nominal Capacitance	30.000pF/ft
Nominal Conductor DCR	24.000 Ohm/1000ft
Nominal Velocity of Propagation	60.0%
Nominal Impedance	75.0 Ohms

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650