



9543 Cable

CONSTRUCTION

Conductor	24 awg (7/0.2mm) stranded tinned copper
Insulation	Colour code: black, white, red, green, orange, blue, white/black, red/black, green/black, orange/black, blue/black, black/white, red/white, green/white, blue/white, black/red, white/red, orange/red, blue/red, red/green, orange/green, black/white/red, white/red/black, red/black/white, green/black/white
Cores	25
Shield	Overall overlapped aluminium-polyester foil, 100% coverage
Drain Wire	24 awg stranded tinned copper
Sheath	Grey PVC Overall diameter: 8.5+/- 0.30mm
BATT Part Number	91029

CHARACTERISTICS

Nominal Capacitance	33.000 pF/ft
Nominal Conductor DCR	25 Ohm

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650