




9696 LSZH Cable

CONSTRUCTION

| | |
|------------|---|
| Conductor | 22 awg solid bare copper |
| Insulation | Polyethylene |
| Pair | 2 twisted pairs, blue & white with blue stripe, orange & white with orange stripe |
| Shield | Overall overlapped aluminium-polyester foil, 100% coverage |
| Braid | Tinned copper (58% coverage) |
| Drain Wire | 22 awg solid tinned copper |
| Sheath | Grey LSZH Overall diameter: 7.36+/- 0.20mm |

BATT Part Number 91357



CHARACTERISTICS

| | |
|---------------------------------|--------------|
| Nominal Capacitance | 52.49 pF/m |
| Nominal Conductor DCR | 46.59 Ohm/km |
| Nominal Velocity of Propagation | 66.0% |
| Nominal Impedance | 100.0 Ohms |

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650