



9841 Cable Computer RS485 Cable

CONSTRUCTION

| | |
|------------------|--|
| Conductor | 24awg (7/32) stranded tinned annealed copper |
| Insulation | Polyethylene |
| Core Colours | white/blue & blue/white |
| Pairs | 1 pair |
| Screen | overall aluminium mylar tape (100% coverage) |
| Braid | tinned copper wire braid (90% coverage) |
| Drain wire | 24 awg stranded tinned copper |
| Sheath | PVC grey nominal overall diameter 5.89mm +/- 0.3mm |
| BATT Part Number | 91149 |



CHARACTERISTICS

| | |
|-------------------------|------------------------|
| Capacitance (cond/cond) | 42 pF/mtr |
| Capacitance (cond/scrn) | 75.4 pF/mtr |
| Conductor Resistance | 78.7 Ohm/km |
| Operating Temperature | -30 deg C to +80 deg C |
| Impedance | 120 Ohms |

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Leeds: 0113 253 3565

Germany: +49 6131 6273874

Birmingham: 0121 313 2870

Manchester: 01204 793111

Italy: +39 2 89656 318

Bristol: 0117 966 6333

Peterborough: 01733 558485

Netherlands: + 31 186 622311

Cardiff: 02920 450044

Teesside: 01642 678633

Singapore: +65 6515 9348

Edinburgh: 0131 333 4400

Belgium: +32 15 20 65 72

Houston: + 1 713 590 1100

Erith: 01322 441165

Denmark: +45 3965 6650