



A2F Brass Flameproof Gland – Premium
A2F Dual Certified – Flameproof EEx'd' and increased safety EEx'e'

Application: Brass gland dual certified flameproof (type d) and increased safety (type e) indoor and outdoor cable gland for use in Zone 1, Zone 2, Zone 21 and Zone 22 Hazardous Areas with all types of unarmoured cables, providing a flameproof seal on the cable outer sheath.

Standards / Approvals: EExd and EExe Dual Certified EN50014, EN50018, EN50019, EN 50281-1-1:1998, EN 60079-0:2004, EN60079-1:2003, EN61241-1:2004
 Ingress Protection: IP66, IP67, IP68
 Lloyds Approval Number: 01/00172
 ABS Approval Number: 01-LD234401-PDA
 DNV Approval Number: E-6157
 SIRA Certificate Number: 02ATEX1057X
 CSA Certificate Number: 1211841

Gland Size	Metric Thread 'C'	Min Thread Length 'D'	Cable diameter 'B'		BATT Part No A2F
			Min	Max	
20/16	20	15	3.1	8.7	-
20s	20	15	6.1	11.7	88515
20	20	15	6.5	14.0	88514
25	25	15	11.1	20.0	88518
32	32	15	17.0	26.3	88519
40	40	15	23.5	32.2	88520
50s	50	15	31.0	38.2	88521
50	50	15	35.6	44.1	88522
63s	63	15	41.5	50	88523
63	63	15	47.2	56	88524
75s	75	15	54.0	52	88525
75	75	15	61.1	68	88526

