

Audio Cable, Two Pair Twin Shielded, 8728

BATT Part No:	91004
Applications:	Audio, communications, instrumentation
Conductor:	22awg (7/30mm) stranded tinned copper
Insulation:	Black and Red, White and Green polypropylene Nominal thickness 0.813
Pair:	2 pair
Individual screen:	Aluminium – mylar tape, 100% coverage
Drain wire:	24 awg (7/32) tinned copper
Individual pair wrap:	Polyester tape (min 15% overlap)
Drain wire:	24 awg (7/32mm) tinned copper
Sheath:	Grey PVC
Overall diameter:	5.46 +/- 0.20mm
Temperature range:	80°C
Characteristics	
Capacitance (cond/cond):	115 pF/3
Capacitance (cond/scrn):	203 pF/m
Conductor resistance:	56 Ohm.km
Nominal velocity of propagation:	66%
Nominal impedance:	50.0 Ohms



Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.