



BW – Brass Indoor Cable Gland – Premium

Application: Brass gland for use with all types of SWA cable. Used on indoor applications not requiring the weather-proof feature of an inner or outer seal. To provide clamping of the armour wire for electrical continuity and mechanical retention of the cable.

SOLO types are offered for installation requiring zero halogen, low smoke and fume glands.

Accessories: As standard, all glands come complete with earth tags, lock nuts and shrouds where required. SOLO types are supplied complete with LSF shroud, locknut and earth tag.

Standards / BW – BS6121: Part 1:2005

Approvals: BW – SOLO – BS6121 Part 1: 2005

SOLO Types are London Underground Ltd Approved

LUL Approval Number R00131

Lloyds Approval Number: 01/00171

ABS Approval Number: 01-LD234401-PDA

SIRA Certificate Number: 99Y9151U

Gland Size	Metric Thread 'C'	Min Thread Length 'D'	Cable Dia 'A' Max	Cable Dia 'B' Max	Armour wire Dia	Max across corners dia 'E'	BATT Part No BW	BATT Part No BW SOLO
20s	20	10	11.6	16.1	0.9/1.25	24.4	88344	88650
20	20	10	13.9	21.1	0.9/1.25	30.0	88345	88651
25	25	10	19.9	27.4	1.25/1.60	36.0	88346	88652
32	32	10	26.2	34.4	1.60/2.00	44.5	88283	88653
40	40	15	32.1	42.4	1.60/2.00	56.3	88284	88654
50s	50	15	38.1	50.1	2.00/2.50	63.4	88349	88655
50	50	15	44.0	55.7	2.00/2.50	72.1	88350	88656
63s	63	15	50.0	62.4	2.50	83.0	88351	88657
63	63	15	55.9	68.2	2.50	88.7	88352	88658
75s	75	15	61.9	76.8	2.50	99.8	88353	88659
75	75	15	67.9	82.9	2.50/3.15	105.3	88354	88660

