



Cat 7 1000 MHz Cable

BATT Part No:	77091
Applications:	IEEE 802.3: Ethernet 10Base-T ; Fast Ethernet 100Base-T ; Gigabit Ethernet 1000Base-T ; 10GBase-T IEEE 802.5 : 16 MB; ISDN ; FDDI ; ATM ; Cable sharing Copper AWG 23/1, bare, 4 pair
Conductor:	SFS-PE
Insulation:	1.38 +/- 0.05mm
Diameter:	IEC 708-1
Colour code:	Plastic laminated aluminium foil
Shielding Pairs:	Copper wire 0.10
Shielding:	Halogen free compound
Jacket:	Orange
Colour:	7.7 +/- 0.2mm
Diameter:	IEC 60811-2-1 (IRM 902, 4h at 70°C)
Chemical Resistance:	86 747 – 10 HH
GL Certificate No:	
Electrical Data:	
Loop resistance:	max. 150 Ohm/km
Insulation resistance:	min .5 GOhm x km at +20°C
Operating capacity:	nom. 45nF/km
Test voltage:	700V/AC
Char. Impedance at 100MHz:	100Ohm +/- 50hm
Velocity of propagation:	app. 0.79c
Signal Term:	Max 425 ns / 100m
Running time difference:	<8 ns / 100m
Screening attenuation at 600MHZ: >100 dB	>100 dB
Coupling resistance:	<6 mOhm/m at 1MHz <3 mOhm/m at 10MHz <3 mOhm/m at 30 MHz
Mechanical Data:	
Temperature range:	-20°C to +60°C 0°C to +50°C
Bending radius:	8 x diameter during installation 4 x diameter fixed
Maximum tractive force	120N
Standards:	Lloyds Marine Type Approval, EN 50288-4-1 ; EN 50173 ; ISO/IEC 11801 2. Output ; IEC 61156-5 EN 60332-1-2 ; EN 60332-3-22 ; EN 61034 ; EN 50267 ; IEC 60754-1 ; IEC 60754-2 ; IEC 61034



Transmission Performance

F in MHz	Attenuation (dB/100m) nom.	NEXT (dB) nom.	ACR (dB/100m) nom.	ELFEXT (dB/100m) nom.	RL (dB) nom.
1	1.7	100	98.3	95	25
4	3.2	100	96.8	93	28
10	5.2	100	94.8	92	30
16	6.5	100	93.5	91	30
20	7.3	100	92.7	90	30
31.25	9.4	100	90.6	86	30
62.5	13.6	100	86.4	82	30
100	17.0	100	83.0	77	30
155	22.2	98	75.8	73	28
200	24.3	95	70.7	70	26
300	30.2	93	62.8	67	25
400	35.2	90	54.8	64	24
500	39.1	87	47.9	62	23
600	43.5	85	41.5	60	23
800	50.0	80	30.0	56	22
900	55.2	78	21.8	53	21
1000	58.1	75	16.9	50	20