



CX Industrial Gland - Premium

- Application:** Brass Gland for use with all types of cable having wire braid armour. Used in applications where it is essential to provide an IP66 deal on the outer sheath and clamping of wire braid for electrical continuity. Approved to BS6121: Part 1: 2005 and BSEN 50262
- Accessories:** As standard, all glands come complete with earth tags, lock nuts and shrouds where required
- Standards:** BS6121: 2005 and BSEN 50262
Lloyds Approval No: 01/00171
ABS Approval No: 01-LD234401-PDA

Gland Size	Metric Thread 'C'	Min Thread length 'D'	Seal Ranges			Max braid thickness	Max across corners 'E'	BATT Part No.
			Cable bedding dia 'A' max	Cable dia 'B'				
				Min	Max			
20/16	20	15	8.6	6.0	13.4	0.8	24.4	88370
20S	20	10	11.6	9.5	15.9	0.8	26.6	88371
20	20	10	13.9	12.5	20.9	0.9	33.3	88372
25	25	10	19.39	17.0	26.2	1.2	40.5	88755
32	32	10	26.2	22.9	33.9	1.4	51.0	88375
40	40	15	32.1	26.0	40.4	1.4	61.0	88376
50S	50	15	38.1	35.0	46.7	1.4	66.5	88377
50	50	15	44.0	38.0	53.1	1.4	77.7	88378
63S	63	15	50.0	45.6	59.4	1.5	83.2	88379
63	63	15	55.9	54.6	65.9	1.5	88.7	88380
75S	75	15	61.9	57.0	72.1	1.5	101.6	88381
75	75	15	67.9	60.4	78.5	1.5	111.1	88382

