



Galvanised steel wire braid flyght pump cable

Conductors:	Annealed flexible copper
Insulation:	VIR (Vulcanised insulated rubber) more commonly known as VRI
Core identification:	3 core: Black, blue & brown, 4 core: Black, blue, brown & green/yellow
Bedding:	TRS (Tough rubber sheath)
Armour/Protection:	GSWB (Galvanised steel wire braid), increased conductivity (58%).
Sheath/Jacket:	PCP (Polyvinylchloride) more commonly known as OFR (Oil resistant & flame retardant)
Colour:	Black with a red stripe
Operating temperature:	Maximum 70°C, minimum bending -20°C
Voltage:	300/500v
Standards:	BS6500: flexible electric cables for use with appliances and equipment intended for domestic, office and similar environments



No of cores and size sqmm	BATT Part No
3 x 1.5	64000
3 x 2.5	64001
4 x 1.5	64002
4 x 2.5	64057
4 x 4	64042

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.