



Li-ICY Screened Control Flexible Cable

Conductors:	Plain annealed flexible copper, Class 5 flexible.
Insulation:	PVC (Polyvinyl chloride)
Core identification:	Cores colour coded to DIN 47100
Screen:	Polyester tape & TCWB (Tinned copper wire braid)
Sheath:	PVC (Polyvinyl chloride)
Colour:	Grey
Voltage:	250v
Operating temperature:	Maximum 80°C, Minimum -20°C
Minimum bending radius:	10 x overall diameter
Standards:	VDE0812 and VDE0814



Size sq.mm	No of cores	Nominal overall diameter mm	Weight	BATT Part No.
0.14	2	3.5	20	79179
0.25	2	3.7	25	79060
0.50	2	5.1	43	79360
0.14	3	3.7	26	79180
0.25	3	4.1	32	79061
0.50	3	5.4	54	79075
0.14	4	4.0	28	79181
0.25	4	4.7	40	79062
0.50	4	6.1	64	79076
0.14	5	4.3	33	79182
0.25	5	5.0	47	79064
0.50	5	6.7	84	79077
0.14	7	4.8	41	79191
0.25	7	5.4	56	79070
0.50	7	7.2	102	79078
0.14	12	6.1	63	79192
0.25	12	7.0	95	79073
0.50	12	9.6	176	79079
0.14	16	6.9	89	79433
0.14	19	7.2	95	79193
0.25	19	8.4	138	79200
0.50	19	11.4	242	79211
0.14	25	8.6	125	79194
0.25	25	10.2	187	79203
0.50	25	13.5	331	79212
0.14	32	9.2	154	79195
0.25	32	10.5	221	79205
0.50	32	15.1	406	79213
0.14	40	10.4	180	79196
0.25	40	12.4	265	79208
0.50	40	16.8	490	79214
0.14	50	11.4	196	79197
0.25	50	13.3	311	79209
0.50	50	19.2	602	79215
0.14	61	12.2	228	79198