



## Molex Euromod LJP Module

### Application:

The Oftel GA5 approved Euromod Line Jack module is fully compatible with the Euromod wall plate range. Designed in accordance with BT specification D22150, the high quality contact and gas tight IDC connection combine to provide a robust low profile product that offers reduced insulation costs and increased flexibility. A labelling facility is provided which is compatible with industry standard 6mm label tapes, for a neat and professional finish. The PBX mastered version contains the necessary bell ring capacitor required for this application.

Robust low profile connector

Shuttered

Compatible with existing range of Euromod modules and accessories

PBX mastered and secondary versions

### Termination tools:

Molex and other industry standard installation tools

### IDC terminations:

Suitable for 0.4mm – 0.6mm solid or stranded cable, max o.d 1.5mm. Two wires may be terminated for daisy chain applications

### Jack connector

### Operating life:

Minimum 1000 insertion cycles

### Contact material:

Phosphor bronze

### Contact plating:

1.25 micrometers Au/Ni

### Material:

UL94-VO Thermoplastic

### IDC Connector

### Operating life:

Minimum 100 reterminations

### Contact material:

Phosphor bronze

### Contact plating:

Sn/Pb over Ni

### Wire size:

2 x 24 – 26 AWG solid or stranded

### Electrical

### D.C Resistance

<100mΩ

### (through 75mm of cordage)

### Insulation resistance:

>100MΩ

### Working voltage:

200Vdc

### Working current:

250mA dc (continuous)

### Black box depth requirements:

16mm secondary, 25mm mastered

### Colour:

White



Part	BATT Part No
6 wire BT6L secondary	78010
6 wire BT6L PBX mastered	78011
6 wire BT6L secondary, angled	78012
6 wire BT6L, PBX mastered, angled	78013

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.

[www.batt.co.uk](http://www.batt.co.uk)

[battindustrial.sales@batt.co.uk](mailto:battindustrial.sales@batt.co.uk)