



N2XS2Y CWS Cable DIN VDE 0276-620 12/20kV

Class 2 stranded bare copper conductors / XLPE insulation / copper wire screen (CWS) / PE sheathed 12/20kV

- Applications:** Suitable for installation in ground, in water, outdoors, indoors and in cable ducts for power stations, industry and distribution networks. The PE sheath permits strong mechanical stress during installation and operation.
- Maximum temperature:** 90°C
- Colour:** Black
- Standards:** DIN VDE 0276 part 620: distribution cables for nominal voltages 3.6 to 20.8/36kV 1kV
- Designation:** N – DIN VDE standard
 2X – XLPE insulation
 S – Copper wire screen
 2Y – PE sheath

No of cores	Conductor size mm	CWS size mm	Diameter overall mm	Weight KG/KM	BATT part number
1	35	16	28	970	16677
1	50	16	29	1150	
1	70	16	31	1350	
1	95	16	32	1650	
1	120	16	34	1900	
1	150	16	35	2150	
1	150	25	35	2250	
1	185	16	37	2550	
1	185	25	37	2600	
1	240	16	40	3100	
1	240	25	40	3200	
1	300	25	42	3800	
1	400	35	45	4750	
1	500	35	48	5800	

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.