



N2XS2Y CWS Cable DIN VDE 0276-620 6/10kV

Class 2 stranded bare copper conductors / XLPE insulation / copper wire screen (CWS) / PE SHEATHED 6/10kV

- Applications:** Suitable for installation in ground, in water, outdoors, indoors and in cable ducts for power stations, industry and distribution networks. The PE sheath permits strong mechanical stress during installation and operation.
- Maximum temperature:** 90°C
- Colour:** Black
- Standards:** DIN VDE 0276 part 620: distribution cables for nominal voltages 3.6 to 20.8/36kV 1kV
- Designation:** N – DIN VDE standard
 2X – XLPE insulation
 S – Copper wire screen
 2Y – PE sheath

No of cores	Conductor size mm	CWS size mm	Diameter overall mm	Weight KG/KM	BATT part number
1	35	16	24	900	16740
1	50	16	25	950	
1	70	16	27	1200	
1	95	16	28	1450	
1	120	16	30	1700	
1	150	16	31	1950	
1	150	25	31	2050	
1	185	16	33	2350	
1	185	25	33	2400	
1	240	16	35	2900	
1	240	25	35	2950	
1	300	25	37	3550	
1	400	35	41	4500	
1	500	35	44	5500	
1	630	35	49	6840	