



N2XSX CWS Cable DIN VDE 0276-620 12/20kV

Class 2 stranded bare copper conductors / XLPE insulation / copper wire screen (CWS) / PVC sheathed 12/20kV

Applications:	Suitable for installation in ground, in water, outdoors, indoors and in cable ducts for power stations, industry and distribution networks.
Maximum temperature:	90°C
Colour:	Red
Standards:	IEC60332-1-2: tests on electric and optical fibre cables under fire conditions Part 1: test for vertical flame propagation for a single insulated wire or cable Section 2: procedure for 1kV pre-mixed flame DIN VDE 0276 part 620: distribution cables for nominal voltages 3.6 to 20.8/36kV 1kV
Designation:	N – DIN VDE standard 2X – XLPE insulation S – Copper wire screen Y – PVC sheath

No of cores	Conductor size mm	CWS size mm	Diameter overall mm	Weight KG/KM	BATT part number
1	35	16	28	1100	
1	50	16	29	1250	
1	70	16	31	1500	
1	95	16	32	1800	
1	120	16	34	2050	
1	150	16	35	2300	
1	150	25	35	2400	
1	185	16	37	2650	
1	185	25	37	2800	
1	240	16	40	3250	
1	240	25	40	3400	
1	300	25	42	4000	
1	400	35	45	4950	
1	500	35	49	6050	
1	630	35	60	9032	

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.

www.batt.co.uk

battindustrial.sales@batt.co.uk



Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.

www.batt.co.uk
battindustrial.sales@batt.co.uk