



N2XSY CWS Cable DIN VDE 0276-620 18/30kV

Class 2 stranded bare copper conductors / XLPE insulation / copper wire screen (CWS) / PVC sheathed 18/30kV

Applications:	Suitable for installation in ground, in water, outdoors, indoors and in cable ducts for power stations, industry and distribution networks.
Maximum temperature:	90°C
Colour:	Red
Standards:	IEC60332-1-2: tests on electric and optical fibre cables under fire conditions Part 1: test for vertical flame propagation for a single insulated wire or cable Section 2: procedure for 1kV pre-mixed flame DIN VDE 0276 part 620: distribution cables for nominal voltages 3.6 to 20.8/36kV 1kV
Designation:	N – DIN VDE standard 2X – XLPE insulation S – Copper wire screen Y – PVC sheath

No of cores	Conductor size mm	CWS size mm	Diameter overall mm	Weight KG/KM	BATT part number
1	50	16	34	1550	16471
1	70	16	36	1750	
1	95	16	37	2050	
1	120	16	39	2350	
1	150	25	40	2700	
1	185	25	42	3100	16715
1	240	25	44	3700	
1	300	25	47	4350	
1	400	35	50	5350	
1	500	35	53	6450	

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.

www.batt.co.uk

battindustrial.sales@batt.co.uk