



NHXCH-FE 180/E 90

Applications:	Security cable with improved fire characteristics
Conductor:	Bare copper conductor, solid or stranded to DIN VDE 0295 cl. 1 or cl.1, BS6360 cl. 1 or 2, IEC 60228 cl ½, HD
Insulation:	Double core insulation of mica tape and cross linked polymer HI1 to DIN VSE 0207 part 23
Colour code:	Colour coding of cores according to DIN VDE 0293-309
Stranding:	Cores stranded in layers
Wrapping:	Glass fibre (also for each single core)
Screen:	Bare copper wire screening with helix of copper tape
Sheath material:	Polyolefin compound type HM4 to DN VDE 0207 part 24
Sheath colour:	Orange
Nominal voltage max:	U _o /U 0.6/1kV
Testing voltage:	4kV
Min bending radius:	12 x diameter
Radiation resistance:	Up to 200 x 10 ⁶ cJ/kg
Temperature range:	-30°C to +70°C
Fire performance:	Flame test to DIN VDE 0482 part 266-2/HD 405.3. BS 4066 part 3 / EN 50266-+2 / IEC 60332-3 (equivalent DIN VSE 0472 part 804 test method C)
Corrosiveness of combustion gases:	According to DIN VDE 0482 part 267/EN 50267-2-2/ IEC 60754-2 (equivalent DIN VDE 0472 part 813)
Smoke density:	According to DIN VDE 0482 part 1034-1 +2, HD 606m DIN EN 61034-1+2/IEC 61034-1+2 (equivalent DIN VDE 0472 part 816).



No pairs x cross section mm ²	Outer diameter ca.mm	Copper weight kg/km	Weight ca.kg/km	AWG no	BATT Part No
2x2.5/2.5 re	15.6	82	321	14	45729
3x1.5/1.5 re	16.9	66	380	16	-
3x2.5/2.5 re	18.30	104	430	14	-
3x4/4 re	19.0	161	530	12	-
3x6/6 re	20.1	240	640	10	-
3x10/10 re	22.0	408	850	8	45727
3x16/16 rm	24.0	643	1150	6	-
3x25/16 rm	28.0	902	1700	4	45724
3x35/16 rm	30.0	1190	2150	2	-
3x50/25 rm	34.0	1723	2800	1	-
3x70/35 rm	38.30	2410	3800	2/0	-
3x95/50 rm	44.0	3296	5100	3/0	-
3x120/70 rm	47.0	4236	6250	4/0	-
3x150/70 rm	51.0	4992	6900	250 MCM	-
3x185/95 rm	56.0	6383	8550	350 MCM	-
3x240/120 rm	65.0	8242	11150	450 MCM	-
4x1.5/1.5 re	18.0	81	435	16	-
4x2.5/2.5 re	18.9	128	500	14	-
4x4/4 re	20.0	200	610	12	-
4x6/6 re	21.0	297	740	10	-
4x10/10 re	23.0	23	1050	8	-
4x16/16 rm	25.0	25	1350	6	-
4x25/16 rm	30.0	30	1950	4	-
4x35/25 rm	33.0	33	2400	2	-

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.



No pairs x cross section mm ²	Outer diameter ca.mm	Copper weight kg/km	Weight ca.kg/km	AWG no	BATT Part No
4x50/16 rm	37.0	37	3200	1	45728
4x70/35 rm	42.0	42	4300	2/0	-
4x95/50 rm	47.0	47	5750	3/0	-
4x120/70 rm	51.0	51	7100	4/0	-
4x150/70 rm	56.0	56	8550	250 MCM	-
4x185/95rm	68.0	68	11020	350 MCM	-
4x240/120 rm	70.0	70	14140	450 MCM	-
5x2.5/2.5 re	-	-	480	14	45725
7x1.5/2.5 re	201.0	21	520	16	-
7x2.5/2.5 re	21.0	21	630	14	45726
12x1.5/2.5 re	27.0	27	770	16	-
12x2.5/4 re	28.0	28	950	14	-
24x1.5/2.5 re	37.0	37	1380	16	-
24x2.5/10 re	37.5	37.5	1750	14	-
30x1.5/6 re	39.0	39	1630	16	-
30x2.5/10 re	39.5	39.5	2080	14	-

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.