



NSGAFOU

Application:	(Class 5) EPR/PCP Black NSGAFOU 1.8/3Kv to VDE 0250 Part 602. Highly Flexible power cables recommended to be used on board of trains underground coaches & Trams. The cable is flame retardant and oil resistant.
Rated Voltage:	1.8/3Kv
Test Voltage:	6Kv
Min ambient temp:	-35 -25
Max operation temp:	+90 °C
Min Laying temp:	-25 °C
Short circuit temp:	250°C
Minimum bending radius:	4 x D to 5 x D
Standards:	VDE Certification, Norms VDE0250
Notes:	Available also as a 3.6/Kv voltage on request.

No. of Cores x Nominal Cross Sectional Area # x mm ²	Nominal Overall Diameter mm	BATT Part Number
1 x 1.5	5.5	22436
1 x 2.5	5.9	22469
1 x 4	6.4	22470
1 x 6	7.0	22471
1 x 10	8.4	22472
1 x 16	9.2	22481
1 x 25	11.5	22482
1 x 35	12.8	22483
1 x 50	14.8	22484
1 x 70	16.0	22485
1 x 95	18.2	22486
1 x 120	19.9	22487
1 x 150	21.8	22488
1 x 185	23.8	22489
1 x 240	26.7	22490
1 x 300	38.0	22491