



### NYM-J

<b>Applications:</b>	House wiring cable. Installation cable.
<b>Conductors:</b>	Conductor material Cu, bare. Green and Yellow available please see table below.
<b>Core colours:</b>	1 core: Green / Yellow 3 core: Green/Yellow, Blue, Brown 4 core: Green/Yellow, Brown, Black and Grey 5 Core: Green/Yellow, Blue, Brown, Black and Grey 7 core: Numbered
<b>Insulation:</b>	PVC
<b>Sheath/Jacket:</b>	PVC
<b>Colour:</b>	Grey
<b>Voltage:</b>	Nominal voltage U0 300 V, Nominal voltage U 500 V
<b>Max. conductor temperature:</b>	70 °C
<b>Operating temperature:</b>	Flexible: -5°C to +70 °C, Fixed: - 40°C to +70 °C
<b>Minimum bending radius:</b>	1 core: 15 x diameter 3 core and above: 4 x overall diameter
<b>Max short circuit temp:</b>	160 °C
<b>Standards:</b>	Flame retardant Acc. EN 50265-2-1



Size	Diameter (approx. mm)	Weight (approx. kg/km)	BATT Part No.
1X1,5	6	40	-
3X1,5	9	111	16842
4X1,5	9	133	16845
5X1,5	10	155	16911
7X1,5	11	196	16915
3X2,5	10	158	16844
4X2,5	11	191	16846
5X2,5	12	225	16912
7X2,5	13	299	16916
1X4	7	73	-
3X4	11	224	16910
4X4	13	284	-
5X4	14	336	16913
1X6	7	94	-
3X6	13	305	-
3X6	13	305	-
4X6	14	374	-
5X6	15	446	16914
1X10	9	141	-
4X10	17	585	-
5X10	18	715	-
1X16	10	210	-
4X16	20	905	-
5X16	22	1119	-
4X25	24	1385	-
5X25	27	1691	-
4X35	27	1850	-

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.