




Reuters Triple Coax Cable

CONSTRUCTION

Inner Conductor	1/0.35mm plain annealed copper
Insulation	1.6+/- 0.05mm foamed PE
Braid	16/6/0.10mm tinned copper wire (coverage: 98%)
Jacket	2.60+/- 0.10mm colour coded PVC
Colour Code	red, green & blue
Filling Yarn	Three strands white filling yarns
Wrapping Tape	One 25mm x 1/2 mil. mylar tape wrapped binder
Rip Cord	White nylon rip cord
Overall Cable Sheath	7.30+/-0.20mm grey PVC, nominal jacket thickness: 0.81mm
BATT Part Number	49194



CHARACTERISTICS

Impedance:	75+/-3 Ohm
Capacitance	60+/-3 pF/M
Attenuation	
20 degree C	
	50MHz 13.0dB/100m
	100MHz 18.90 dB/100m
	200MHz 27.90 dB/100m
	400MHz 41.55 dB/100m
	1000MHz 75.16 dB/100m

www.batt.co.uk

battindustrial.sales@batt.co.uk

Aberdeen: 01224 897979

Erith: 01322 441165

Copenhagen: +45 3965 6650

Birmingham: 0121 313 2870

Leeds: 0113 253 3565

Houston: + 1 713 590 1100

Bristol: 0117 966 6333

Manchester: 01204 793111

Mainz: +49 6131 6273874

Cardiff: 02920 450044

Peterborough: 01733 558485

Rotterdam: + 31 186 622311