



## RG214 LSZH Cable

to American Military Spec MIL

### CONSTRUCTION

Inner Conductor	7/0.75mm silver plated stranded copper wires 3.2mm <sup>2</sup>
Insulation	PE 7.25mm <sup>2</sup>
1st Braid	silver plated CWB (coverage: 94%)
2nd Braid	silver plated CWB (coverage: 97%)
Sheath	black LSZH

BATT Part Number 49195

Application Coaxial cables are used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions.



### CHARACTERISTICS

Impedance:	50 Ohm
Capacitance	100 pF/M
Attenuation	50MHz 4.9 dB/100m
20 degree C	400MHz 15.1dB/100m
	1000MHz 26.5 dB/100m
	3000MHz 50.6 dB/100m
	5200MHz 67.8 dB/100m
Temperature Range	-40°C to 85°C

[www.batt.co.uk](http://www.batt.co.uk)

[battindustrial.sales@batt.co.uk](mailto:battindustrial.sales@batt.co.uk)

Aberdeen: 01224 897979

Erith: 01322 441165

Copenhagen: +45 3965 6650

Birmingham: 0121 313 2870

Leeds: 0113 253 3565

Houston: + 1 713 590 1100

Bristol: 0117 966 6333

Manchester: 01204 793111

Mainz: +49 6131 6273874

Cardiff: 02920 450044

Peterborough: 01733 558485

Rotterdam: + 31 186 622311

Edinburgh: 0131 333 4400

Teesside: 01642 678633