

RG59 + 1 Pair 22 awg PVC Figure 8

BATT Part No:	91005
RG59	
Conductor:	22awg (7/0.254mm) bare stranded copper
Insulation:	Foam PE diameter: 3.71 +/- 0.10mm
Braid:	16/8/0.12mm bare copper braiding, min. 95% coverage Foil shielded twisted pair 22 awg
Foil shielded twisted pair 22 awg	
Insulation:	black & red PVS diameter: 1.37+/-0.10mm
Pair:	1 twisted pair, black & red
Drain wire:	22 awg (7/0.254mm) stranded tinned copper
Shield:	Overlapped aluminium-polyester foil, 100% coverage
RG59 & foil shielded cable with common sheath, figure 8	
Sheath:	PVC
Colour:	Black
Overall Diameter:	6.15 +/- 0.15mm x 11.94 +/- 0.15mm
Nominal capacitance:	17.3 pF/ft
Nominal conductor DCR:	15.000 Ohm/ 1000ft
Nominal velocity of propagation:	78%
Nominal impedance:	75 Ohms
Capacitance:	1 MHz: 0.3 dB/100Ft 5 MHz: 0.7 dB/100Ft 10 MHz: 1.0 dB/100Ft 50 MHz: 2.1 dB/100Ft 100 MHz: 3.0 dB/100Ft

