

## RS422 Shielded & Braided Computer Cable 8162,8163

<b>Conductor:</b>	24 awg stranded tinned copper
<b>Insulation:</b>	Polypropylene
<b>Colour:</b>	Grey
<b>Shield:</b>	Each pair individual and overall aluminium-polyester foil, 100% coverage
<b>Drain Wire:</b>	24 awg stranded tinned copper
<b>Braid:</b>	Tinned copper wire braid (65% coverage)
<b>Nominal Capacitance:</b>	41.000 pF/m
<b>Nominal Conductor DCR:</b>	78.74 Ohm/km
<b>Nominal Velocity of Propagation:</b>	78.0%
<b>Nominal Impedance:</b>	100.0 Ohms

### 8162

<b>BATT Part No:</b>	91320
<b>Pair:</b>	2 twisted pairs: black & red, black & white
<b>Sheath:</b>	PVC
<b>Overall diameter:</b>	8.92+/- 0.20mm

### 8162 LSZH

<b>BATT Part No:</b>	91448
<b>Pair:</b>	2 twisted pairs: black & red, black & white
<b>Sheath:</b>	LSZH
<b>Overall diameter:</b>	8.92+/- 0.20mm

### 8163

<b>BATT Part No:</b>	91150
<b>Pair:</b>	3 twisted pairs, black & red, black & white, black & green
<b>Sheath:</b>	PVC
<b>Overall diameter:</b>	9.1+/- 0.20mm

### 8163 LSZH

<b>BATT Part No:</b>	91449
<b>Pair:</b>	3 twisted pairs, black & red, black & white, black & green
<b>Sheath:</b>	LSZH
<b>Overall diameter:</b>	9.1+/- 0.20mm

