

RUBBER FLATFORM NGFLGOEU

Flexible plain annealed copper conductors/EPR insulated to VDE0207 part 20/PCP (polychloroprene) rubber sheathed, 300/500 volts grade

SIZE SQ.MM	CLASS OF CONDUCTOR	NUMBER OF CORES	BATT PART NUMBER	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.5	5	4	25005	6.2 x 17.5	200
2.5	5	4	25006	7.5 x 21.0	280
4	5	4	25035	9.0 x 26.0	410
6	5	4	25034	9.5 x 29.0	600
10	5	4	25037	11.0 x 33.0	800
16	5	4	25039	13.0 x 38.0	1150
25	5	4	25040	15.0 x 49.5	1700
35	5	4	25064	17.0 x 55.0	2200
50	5	4		19.0 x 63.0	3000
70	5	4	25027	22.0 x 71.0	4000
1.5	5	8	25008	6.2 x 31.5	370
2.5	5	8		7.5 x 39.0	550
1.5	5	12	25012	6.5 x 47.0	620
2.5	5	12	25013	8.0 x 56.0	800

Maximum conductor temperature:90°C, **Minimum flexing** -35°C

Core Identification:

4 Core - Black, Grey, Green/Yellow & Brown
 5 Core plus, Printed numbers with One Green/Yellow Core

This cable is also manufactured in a PVC configuration

Applications: Suitable for hoisting control systems on overhead cranes



battindustrial.sales@batt.co.uk