

Sen5e Cat 5e Module

BATT Part No:	54026
Description:	Sen5e 25x50mm RJ45 modules provide a solution to the installation of communication outlets where depth bedding the faceplate is at a premium. This unique design is available as UTP and has a maximum overall depth of only 27mm and protrudes just 18mm into a back box. Sen5e modules are ideal for floor boxes and shallow trunking where space is critical. Mounting frames and 12.5, 25 and 50mm blanks are also available.
Termination procedures:	Place the rear part of the module on a flat surface with the IDC terminals facing upwards. Strip cable outer jacket back 30mm. Place the cable between the IDC blocks, trying not to untwist the pairs more than is necessary. Carefully punch down each conductor using a KRONE IDC tool. For 568B (258A) wiring, see colour coding on IDC terminals. Trim excess wire. Be sure to secure cable or the module with the tie wrap provided. Securing clip is located between the rear of the jack and the IDC connectors.
IDC Terminals:	Accept 22-26 AWG solid or stranded conductors
Jack housing:	Black polyester meeting UL 94-VO
Jack contacts:	Phosphor bronze, gold over nickel
Current/voltage rating:	1.5 amp / 30 VAC. 42VDC
Dielectric withstanding:	1000 volts RMS at 60Hz for 1 min
Insulation resistance:	500 MOhms for 1 min

