

Trunk/baseband Coax Cable Ref 9880

BATT Part No:	91114
Applications:	Coaxial cables are used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions.
Conductor:	12awg solid bare copper
Insulation:	6.17+/- 0.05mm foam PE
Tape:	Overall aluminium foil tape
Braid:	Tinned copper wire (coverage: 94%)
Tape:	Overall aluminium foil tape
Braid:	Tinned copper wire (coverage: 90%)
Sheath:	10.28+/- 0.20mm PVC
Colour:	Yellow
Impedance:	50+/-3 Ohm
Capacitance	85+/-5 pF/M
Attenuation at 20°C:	100MHz 5.5 dB/100m
	400MHz 12.7 dB/100m
	1000MHz 22.6 dB/100m
Velocity ratio:	78%
Rated voltage:	30V



Trunk/baseband Coax Cable Ref 9880 LSZH

BATT Part No:	Yellow: 91427 Blue: 91363
Applications:	Coaxial cables are used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions.
Conductor:	12awg solid bare copper
Insulation:	6.17+/- 0.05mm foam PE
Tape:	Overall aluminium foil tape
Braid:	Tinned copper wire (coverage: 94%)
Tape:	Overall aluminium foil tape
Braid:	Tinned copper wire (coverage: 90%)
Sheath:	10.28+/- 0.20mm PVC
Colour:	Yellow or blue
Impedance:	50+/-3 Ohm
Capacitance	85+/-5 pF/M
Attenuation at 20°C:	100MHz 5.5 dB/100m
	400MHz 12.7 dB/100m
	1000MHz 22.6 dB/100m
Velocity ratio:	78%
Rated voltage:	30V

