



## Twin Axial Cable Ref 9207

<b>BATT Part Number:</b>	91431
	SWA: 91432
<b>Conductor:</b>	20awg (7/0.32mm) , one tinned copper conductor, one plain copper conductor
<b>Insulation:</b>	Natural & natural PE
<b>Pair:</b>	1 twisted pair
<b>Shield:</b>	Overlapped aluminium-polyester foil, 100% coverage
<b>Braid:</b>	Tinned copper wire braid
<b>Inner sheath:</b>	PVC
<b>Armour:</b>	None
	SWA: Steel wire armour
<b>Sheath:</b>	Black PVC
<b>Overall diameter:</b>	8.38 +/- 0.20mm
<b>Nominal Capacitance:</b>	14.5 pF/ft
<b>Nominal Conductor DCR:</b>	9.5 Ohm/100ft
<b>Nominal Velocity of Propagation</b>	100 Ohms
<b>Nominal Impedance:</b>	45.0 Ohms
	SWA: 100 Ohms

Whilst BATT CABLES plc endeavours to ensure the information on the website, specification sheets and all other technical information is accurate, the information is for guidance only and it is subject to change without notice or liability. Batt Cables Plc is not responsible for the consequences of any inadequacies, inaccuracies or other deficiencies contained therein. When selecting cable accessories, please note that the actual cable dimensions may vary due to manufacturing tolerances.