

## URM TYPE TO BS EN 50117

URM NUMBER	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM	IMPEDANCE OHMS	TEMP RATING ° C	JACKET COLOUR	BATT PART NUMBER
43	5.0	40	50	70	Black	49003
67	10.3	160	50	70	Black	49010
67-SWA	14.1	382	50	70	Black	49087
76	5.0	40	50	70	Black	49017
112	11.0	210	50	70	Grey	49029
57	10.3	150	75	70	Black	49005
70	5.8	60	75	70	Black	49012
70-SWA	9.8	192	75	70	Black	49013
90	6.0	66	75	70	Black	49018
DRM 68	6.8	90	100	70	Black	49086
108	4.5	45	50	200	Brown	49025
109	2.5	150	50	200	Brown	49026
110	1.8	9	50	200	Brown	49027
106	5.3	60	75	200	Brown	49023
111	2.5	8	75	200	Brown	49028



URM NUMBER	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM	IMPEDANCE OHMS	TEMP RATING ° C	JACKET COLOUR	BATT PART NUMBER
67-LSF	10.3	160	50	70	Black	49139
70-LSF	5.8	60	75	70	Black	49089

DIMENSIONS OF URM COAXIAL CABLE													
URM NUMBER	43	67	76	95	57	70	D68	107	108	109	110	106	111
Impedance (Ohms)	50	50	50	50	75	75	100	50	50	50	50	75	75
Temp Rating °C (max)	70	70	70	70	70	70	70	200	200	200	200	200	200
Inner Cond. Size (sq.mm)	0.65	3.2	0.56	0.17	1.0	0.19	2X0.35	3.7	0.79	0.19	0.07	0.33	0.05
No. wires/size (mm)	11.9	7/7.6	7/3.2	1/4.6	1/1.15	7/0.19	2X7/25	7/8.2	7/1.0	7/1.18	7/1.1	1/6.5	7/1.0
Type Cond.	PAC	PAC	PAC	SCCS	PAC	PAC	PAC	SPC	SPC	SCCS	SCCS	SCCS	SCCS
Type Insulation	PE(S)	PE(S)	PE(S)	PE(S)	PE(S)	PE(S)	PE(S)	PTFE	PTFE	PTFE	PTFE	PTFE	PTFE
Dia. Insulation (mm)	2.95	7.25	2.95	1.5	7.25	3.25	1.75	7.25	2.95	1.5	0.87	3.7	1.5
Type outer cond.	PCWB	PCWB	PCWB	PCWB	PCWB	PCWB	LTCWB	SPCWB	SPCWB	SPCWB	SPCWB	SPCWB	SPCWB
Dia. outer cond.(mm)	3.63	8.15	3.63	1.95	8.15	3.93	5.3	8.15	3.63	1.95	1.32	4.38	1.95
Type outer sheath	PVC	PVC	PVC	PVC	PVC	PVC	PVC	FEP	FEP	FEP	FEP	FEP	FEP
Dia. outer sheath (mm)	5.0	10.3	5.0	2.3	10.3	5.8	6.75	9.0	4.5	2.45	1.8	5.25	2.45
Col. outer sheath	BLACK	BLACK	BLACK	BLACK	BLACK	BLACK	BLACK	BROWN	BROWN	BROWN	BROWN	BROWN	BROWN
Min. bend radius 'x O/D'	5	5	5	5	5	5	5	5	5	5	5	5	5
Weight Kg/Km	40	160	40	10	150	60	90	180	45	15	8.5	60	8
Nom. capacitance (pF/m)	100	100	100	100	67	67	52	96	94	94	92	63	63

[battindustrial.sales@batt.co.uk](mailto:battindustrial.sales@batt.co.uk)