



VG-YMvKasmb 0.6/1Kv

Class 1 copper conductor / XLPE insulation / PVC bedded / GSWA and ECC / PVC. Flame retardant sheath to BSEN50266.

- Application:** Power cable for use in industrial applications.
Suitable for underground laying
- Sheath colour:** Grey
- Voltage rating:** 600/1000 volts
- Conductor identification:** 3 core – Black, Brown and Grey
4 core – Black, Brown, Grey and Blue
5 core – Black, Brown, Grey, Blue and Black
- Operating temperature:** Maximum 90°C Minimum bending 0°C
- Minimum bending radius:** 12 x overall diameter
- BSEN50266-2-4:** Common test methods for cable under fire conditions. Test for vertical flame spread of vertically mounted bunched wires or cables Part 2-4 Procedures category C
- Designation:** V – PVC mb outer sheath
G – Steel wire armour
Y – XLPE conductor insulation
M
V – PVC inner sheathing
K
As – Earth shield
Mb – flame retardant
- Approvals:** KEMA approved



No of cores	Conductor size mm	Conductor class	Approx diameter overall mm	Weight kg/km	BATT part number
3	1.5	1	14	445	
3	2.5	1	15		
4	1.5	1	14		
4	2.5	1	15	740	55031
4	4.0	1	16		
4	6.0	1	18		
4	10	1	21		
4	50	1	32		
5	1.5	1	15	1014	55090
5	2.5	1	16		
5	6.0	1	18		
5	16	1	26		
5	16	1	26		
				2910	55073
				2910	55219
				1685	55218