

Unarmoured power & control cable



XLPE Marine Cable

Class 2 copper conductor to IEC60228, XLPE insulation to IEC60092-351, separator bedding tape, LSZH sheath to IEC60092-359 Voltage rating: 0.6/1KV
Sheath colour: Black

NO OF CORES	CONDUCTOR SIZE MM	OVERALL DIAMETER MM	WEIGHT KG/KM	CURRENT RATING AMPS	MIN BENDING RADIUS MM	BATT CABLES PART NUMBER
1	6	6.5	95	52	30	
1	10	7.5	140	72	30	
1	16	8.5	205	96	35	
1	25	11.5	320	127	50	
1	35	12.0	420	157	50	
1	50	14.0	555	196	60	
1	70	17.0	790	242	70	
1	95	18.0	1040	293	75	14317
1	120	20.0	1300	339	80	
1	150	23.5	1610	389	95	
1	185	26.0	2005	444	160	14318
1	240	29.0	2615	522	175	
1	300	32.0	3235	601	195	
2	1.5	8.0	80	20	35	14308
2	2.5	10.0	115	26	40	14311
2	4	11.0	155	34	45	14313
2	6	11.5	205	44	50	
2	10	14.5	315	61	60	14315
2	16	16.5	465	82	70	
2	25	20.5	700	108	85	
2	35	23.5	990	133	95	
3	1.5	8.5	100	16	35	14309
3	2.5	10.5	145	21	45	14312
3	4	11.0	200	28	45	14314
3	6	12.5	280	36	50	
3	10	15.5	425	50	65	
3	16	18.0	630	67	75	
3	25	21.5	960	89	90	
3	35	25.0	1335	110	150	
3	50	28.5	1785	137	175	
3	70	33.5	2570	169	205	
3	95	37.5	3380	205	225	
3	120	42.0	4255	237	255	
3	150	48.0	5235	272	290	
4	1.5	9.5	135	16	40	
4	2.5	11.5	180	21	50	
4	4	13.0	260	28	55	
4	6	14.5	355	36	60	
4	10	17.0	545	50	70	
4	16	20.0	820	67	80	
4	25	24.0	1265	89	100	
4	35	27.0	1725	110	165	
4	50	32.0	2325	137	195	
4	70	38.0	3325	169	230	
4	95	43.0	4425	205	260	
4	120	47.5	5515	237	285	



